



恒和化工
Henghe Chemical

GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD

TOP 5TH BIGGEST MANUFACTURER OF SYNTHETIC ADHENSIVES, ACRYLIC EMULSIONS IN CHINA

Hanhe Industrial Park, Jinli, Gaoyao, Zhaoqing, Guangdong, China

Tel :86-758-8591688 EXT:831

Fax:86-758-8591666

Web: <http://emulsion.en.alibaba.com>

Email: alexgwong@hotmail.com

TECHNICAL DATA SHEET

LR-6860

Granite Paint Emulsion

LR-6860 is a kind of acrylic synthetic emulsion. LR-8601 is polymerized with the proprietary technology of Henghe chemical.

Parameter:

Polymer Types	Acrylate Copolymer
Physical Appearance	Milky White With Blue Light
Solid Content (%)	45±1
Viscosity (CPS)	4000-8000
MFFT(°C)	24
Tg(°C)	34
pH value	7.0-9.0
Application	Exterior Wall Latex Paint and True Stone Paint Varnish
Part	Anion
Characteristics	No APEO Excellent Whitening Resistance and Water Recovery Excellent Weather Resistance and Yellowing Resistance Color Difference Is Small Between High and Low Temperature

Note: The above is the typical nature of the product. It can not be regarded as the product specifications. Please refer to the specific COA. Storage temperature should be 10 °C ~ 35°C, avoid direct sunlight, if possible, should be used within 12 months.

These technical data are solely to describe the product. They are not subject to constant monitoring or part of specification. The opinions expressed herein are those of expert within GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD. We believe that the information contained herein is current as of the date of this Data Technical Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD., it is the user's obligation to determine the conditions of safe use of the products.

