



恒和化工
Henghe Chemical

GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD

TOP 5TH BIGGEST MANUFACTURER OF SYNTHETIC ADHENSIVES, ACRYLIC EMULSIONS IN CHINA

Hanhe Industrial Park, Jinli, Gaoyao, Zhaoqing, Guangdong, China

Tel :86-758-8591688 EXT:831

Fax:86-758-8591666

Web: <http://emulsion.en.alibaba.com>

Email: alexgwong@hotmail.com

TECHNICAL DATA SHEET

LR-6318

Granite Paint Emulsion

LR-6318 is an organic silicone modified acrylic compound emulsion, which is a special emulsion of 100% genuine acrylic paint modified by pure acrylic emulsion.

Parameter:

Polymer Types	Pure Acrylic Emulsion
Physical Appearance	Milky White
Solid Content(%)	46±1
Viscosity(CPS)	1500-4500
MFFT(°C)	20
Tg(°C)	36
pH value	7.0-9.0
Application	Granite Paint
Characteristics	Synthesis Polymerization Without Soap Excellent Water-whitening Resistance and Water-whitening Recovery Excellent Weather and Yellow Resistance Tensile Paint Film Good Adhesion

Note: The above is the typical nature of the product. It can not be regarded as the product specifications. Please refer to the specific COA. Storage temperature should be 10 °C ~ 35°C, avoid direct sunlight, if possible, should be used within 12 months.

These technical data are solely to describe the product. They are not subject to constant monitoring or part of specification. The opinions expressed herein are those of expert within GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD. We believe that the information contained herein is current as of the date of this Data Technical Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD., it is the user's obligation to determine the conditions of safe use of the products.

SGS