



恒和化工
Henghe Chemical

GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD

TOP 5TH BIGGEST MANUFACTURER OF SYNTHETIC ADHENSIVES, ACRYLIC EMULSIONS IN CHINA

Hanhe Industrial Park, Jinli, Gaoyao, Zhaoqing, Guangdong, China

Tel :86-758-8591688 EXT:831

Fax:86-758-8591666

Web: <http://emulsion.en.alibaba.com>

Email: alexgwong@hotmail.com

TECHNICAL DATA SHEET

LR-6618

High Performance Texture Paint Emulsion

LR-6618 High performance texture paint emulsion is a kind of styrene acrylate copolymer emulsion, which is polymerized by Henghe special technology. Acrylate core-shell copolymerization technology gives the emulsion special viscosity structure, which is effective bridging wall micro-cracks. Highly active ions transform into narrow particle size, which makes the emulsion with the characteristics of excellent color rendering, excellent scraping performance, not easy to stick knife, texture fashionable and natural.

Parameter:

Polymer Types	Styrene Acrylate Copolymer
Physical Appearance	Milk White With Blue White
Solid Content (%)	48±1
Viscosity (CPS)	3000-8000
MFFT(°C)	20
Tg(°C)	28
pH value	7.0-9.0
Application	High Grade Texture Paint
Particle size	0.1-0.2 micron
Characteristics	Excellent Film-forming Effect Excellent Water Resistance and Impermeability Excellent Weather Resistance and Yellowing Resistance No Peeling, No Cracking

Note: The above is the typical nature of the product. It can not be regarded as the product specifications. Please refer to the specific COA. Storage temperature should be 10 °C ~ 35°C, avoid direct sunlight, if possible, should be used within 12 months.

These technical data are solely to describe the product. They are not subject to constant monitoring or part of specification. The opinions expressed herein are those of expert within GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD. We believe that the information contained herein is current as of the date of this Data Technical Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD., it is the user's obligation to determine the conditions of safe use of the products.

