



恒和化工  
Henghe Chemical

# GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD

TOP 5TH BIGGEST MANUFACTURER OF SYNTHETIC ADHENSIVES, ACRYLIC EMULSIONS IN CHINA

Hanhe Industrial Park, Jinli, Gaoyao, Zhaoqing, Guangdong, China

Tel :86-758-8591688 EXT:831

Fax:86-758-8591666

Web: <http://emulsion.en.alibaba.com>

Email: alexgwong@hotmail.com

## TECHNICAL DATA SHEET

### LR-6803A

### Modified Styrene Acrylic Emulsion

LR-6803A synthetic emulsion is a kind of modified styrene acrylic waterproof emulsion. It is especially suitable for making waterproof coating for construction.

**Parameter:**

<b>Polymer Types</b>	Styrene Acrylic Copolymer
<b>Physical Appearance</b>	Translucent
<b>Solid Content (%)</b>	36±1
<b>Viscosity (CPS)</b>	30000-50000
<b>MFFT(°C)</b>	5
<b>Tg(°C)</b>	28
<b>pH value</b>	7.0-9.0
<b>Application</b>	Transparent Waterproof Coating
<b>Particle size</b>	0.1-0.2 um
<b>Characteristics</b>	Excellent Water Whitening Resistance High Permeability and Good Adhesion Excellent Consistency, Not Easy To Sag Convenient Operation and Direct Construction

**Note:** The above is the typical nature of the product. It can not be regarded as the product specifications. Please refer to the specific COA. Storage temperature should be 10 °C ~ 35°C, avoid direct sunlight, if possible, should be used within 12 months.

These technical data are solely to describe the product. They are not subject to constant monitoring or part of specification. The opinions expressed herein are those of expert within GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD. We believe that the information contained herein is current as of the date of this Data Technical Sheet. Since the use of this information and of these opinions and the conditions of use of this product are not within the control of GUANGDONG HENGHE YONGSHENG INDUSTRIAL CO.,LTD., it is the user's obligation to determine the conditions of safe use of the products.

